Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

(Currently Amended) An image generation system comprising:

 a memory which stores a program and data for image generating; and
 at least one processor which is connected to the memory and performs

 processing for image generating,

the processor performing:

depth cueing for an object on condition that the object is positioned within a depth cueing area such that the color of the object being more distant from a viewpoint is made closer to a target color;

varying an alpha (a) value of the object on condition that the object is positioned within a depth cueing area so that the object being more distant from the viewpoint becomes more transparent;

sorting objects of which alpha values are varied so that the objects are drawn in succession starting from an object nearest to the viewpoint; and

drawing an image viewable from a virtual camera in an object space in drawing order determined by the sorting processing while performing hidden-surface erasing based on a Z-buffer process for the objects of which alpha values are varied.

 (Previously Presented) The image generation system as defined in claim 1, the processor further performing:
 drawing a most distant background including a color different from the target

3-4. (Canceled).

color.

5. (Previously Presented) The image generation system as defined in claim 1, the processor further performing:

varying a depth cueing value for each vertex of the object based on a Z-value for each vertex of the object; and

varying the alpha value for each vertex of the object based on the Z-value for each vertex of the object.

6. (Previously Presented) The image generation system as defined in claim 2, the processor further performing:

varying a depth cueing value for each vertex of the object based on a Z-value for each vertex of the object; and

varying the alpha value for each vertex of the object based on the Z-value for each vertex of the object.

- 7-9. (Canceled)
- 10. (Currently Amended) An image generation system comprising:

 a memory which stores a program and data for image generating; and
 at least one processor which is connected to the memory and performs
 processing for image generating,

the processor performing:

varying an alpha (α) value of an object depending on the distance between the object and the viewpoint on condition that the object is positioned within a depth cueing area;

sorting objects of which alpha values are varied so that the objects are drawn in succession starting from an object nearest to the viewpoint; and

drawing an image viewable from a virtual camera in an object space in drawing order determined by the sorting processing while performing hidden-surface erasing based on a Z-buffer process for the objects of which alpha values are varied.

11. (Currently Amended) A computer-usable program embodied on an information storage medium or in a carrier wave, comprising a processing routine for implementing:

depth cueing for an object on condition that the object is positioned within a depth cueing area such that the color of the object being more distant from a viewpoint is made closer to a target color;

varying an alpha (a) value of the object on condition that the object is positioned within a depth cueing area so that the object being more distant from the viewpoint becomes more transparent;

sorting objects of which alpha values are varied so that the objects are drawn in succession starting from an object nearest to the viewpoint; and

drawing an image viewable from a virtual camera in an object space in drawing order determined by the sorting processing while performing hidden-surface erasing based on a Z-buffer process for the objects of which alpha values are varied.

12. (Previously Presented) The program as defined in claim 11, further comprising a processing routine for implementing:

drawing a most distant background including a color different from the target color.

- 13-14. (Canceled).
- 15. (Previously Presented) The program as defined in claim 11, further comprising a processing routine for implementing:

varying a depth cueing value for each vertex of the object based on a Z-value for each vertex of the object; and

varying the alpha value for each vertex of the object based on the Z-value for each vertex of the object.

16. (Previously Presented) The program as defined in claim 12, further comprising a processing routine for implementing:

varying a depth cueing value for each vertex of the object based on a Z-value for each vertex of the object; and

varying the alpha value for each vertex of the object based on the Z-value for each vertex of the object.

17-19. (Canceled).

20. (Currently Amended) A computer-usable program embodied on an information storage medium or in a carrier wave, comprising a processing routine for implementing:

varying an alpha (α) value of an object depending on the distance between the object and the viewpoint on condition that the object is positioned within a depth cueing area;

sorting objects of which alpha values are varied so that the objects are drawn in succession starting from an object nearest to the viewpoint; and

drawing an image viewable from a virtual camera in an object space in drawing order determined by the sorting processing while performing hidden-surface erasing based on a Z-buffer process for the objects of which alpha values are varied.

21. (Currently Amended) An image generation method comprising:

depth cueing for an object on condition that the object is positioned within a

depth cueing area such that the color of the object being more distant from a viewpoint is

made closer to a target color;

varying an alpha (a) value of the object on condition that the object is positioned within a depth cueing area so that the object being more distant from the viewpoint becomes more transparent;

sorting objects of which alpha values are varied so that the objects are drawn in succession starting from an object nearest to the viewpoint; and

drawing an image viewable from a virtual camera in an object space in drawing order determined by the sorting processing while performing hidden-surface erasing based on a Z-buffer process for the objects of which alpha values are varied.

22. (Original) The image generation method as defined in claim 21, further comprising:

drawing a most distant background including a color different from the target color.

- 23-24. (Canceled).
- 25. (Original) The image generation method as defined in claim 21, further comprising:

varying a depth cueing value for each vertex of the object based on a Z-value for each vertex of the object; and

varying the alpha value for each vertex of the object based on the Z-value for each vertex of the object.

26. (Original) The image generation method as defined in claim 22, further comprising:

varying a depth cueing value for each vertex of the object based on a Z-value for each vertex of the object; and

varying the alpha value for each vertex of the object based on the Z-value for each vertex of the object.

27. (Currently Amended) An image generation method comprising:

varying an alpha (α) value of an object depending on the distance between the object and the viewpoint on condition that the object is positioned within a depth cueing area;

sorting objects of which alpha values are varied so that the objects is drawn sequentially from an object nearest to the viewpoint; and

drawing an image viewable from virtual camera in an object space in drawing order determined by the sorting processing while performing hidden-surface erasing based on Z-buffer process for the objects of which alpha values are varied.